

Packed with a ton of advanced features, MEIKO's undercounter and door type dish machines set the standard for getting it done.

- > Exclusive Auto-Safe system ensures correct wash and sanitizing rinse temperatures, using ANY incoming water temperature
- > Sloped ceilings to help prevent soiled water from dripping on sanitized ware — or on the operator
- > Automatic self-cleaning cycle at shutdown
- > Exclusive Aqua-Stop feature automatically shuts down the machine if an internal water leak is detected
- > Flush-paneled, double-walled stainless steel construction for operator safety, easier cleaning and improved efficiency
- > Built-in booster heater
- > Pumped final rinse ensures constant pressure for consistent and outstanding results
- > Exclusive Soft Start feature starts the wash pump slowly and gradually builds water pressure, protecting fragile ware from shifting or breaking
- > Stainless steel wash and rinse arms with slotted, concave nozzles to minimize clogging
- > Exclusive Active Plus double filtration system strips soil out of the wash water, conserving detergent and easing cleanup
- > Pumped drain feature allows the use of a wall-mounted drain



FV 40.2 | Undercounter Dishwasher



MEIKO's FV 40.2 undercounter machine combines state-of-the-art, labor-saving technology with outstanding, super-efficient performance – all in a space-saving, get-it-done, package.

CAPACITY:
37 racks/hr., 925 dishes/hr.


WATER CONSUMPTION:
24.4 gals./hr., 0.66 gals./rack

WATER SUPPLY TEMPERATURE:
Any; 140°F recommended

WASH PUMP:
3/4 hp.

OPTIONS:
Roller base, power cord kit, stand, cabinet stand, drain tempering

VOLTAGES:
208-230V / 60Hz / 1Ph
208-230V / 60Hz / 3Ph



FV 40.2 G | Undercounter Glasswasher



The FV 40.2 G has all of the great features of the standard FV 40.2, but in a smaller size optimized for use in bars, coffee houses, and kiosks. Standing only 29 1/2" tall, the FV 40.2 G fits beneath shorter countertops, but delivers the same great results as the FV 40.2.

CAPACITY:
37 racks/hr., 1,332 glasses/hr.

WATER CONSUMPTION:
24.4 gals./hr., 0.66 gals./rack

WATER SUPPLY TEMPERATURE:
Any; 140°F recommended

WASH PUMP:
3/4 hp.

OPTIONS:
Roller base, power cord kit, stand, cabinet stand, drain tempering

VOLTAGES:
208-230V / 60Hz / 1Ph
208-230V / 60Hz / 3Ph

